


Blondelle 2 lane Manifold, Ø 100, aluminium body

All refrigerants in one manifold.



- All combinations of refrigerants possible, up to 6 on 1 dial.
- Unique spindle valves, always tight without effort
- Class 1, 'A Lame Acier' gauges
- Ø 100, pulse-free

- 2 lane manifold
- Sight glass and hook
- Available with or without the appropriate charging hoses

Supplied in a Blondelle plastic carrying case including: 3 charging hoses, red, yellow and blue; length 1 m with 1/4" SAE fitting. Option: 1/4" SAE – 5/16" SAE adaptors

Material	Other	Gauges		Reference			Scales		
		Diameter	Type	Manifold	Dial	Option	bar	psi	Refrigerants
Aluminium	Complete case	100 mm	Pulse-free	FR5802	E100		x		R22+R134a+R404A+R410A+R407C vap/liq
						A			Description of the option
									2 1/4" SAE-5/16" SAE adaptors

Other refrigerant combinations are possible, check out p24 (Blondelle D100 gauge) & contact Panimpex.

How to read the tables?

The complete designation of a manifold comprises on one hand the references of the manifold and gauge and on the other hand the reference of the refrigerants.

Ex: 2lane aluminium manifold, charging hoses, 100mm gauges, pulse-free, refrigerants: R22+R134a+R404A+R410A+R407C Vap.Liq.: Manifold: FR5802; Refrigerants: E100; Reference: FR5802-E100