



# Blondelle 4 lane Manifold, aluminium body

Central valve



- Unique spindle valves, always tight without effort
- Class 1, 'A Lame Acier' Ø 80 gauges
- 4 lanes - Central Valve
- All combinations of refrigerants possible
- Dry, oil filled or pulse-free
- Sight glass and hook
- Available with or without the appropriate charging hoses

Supplied in a Blondelle plastic carrying case including: 3 charging hoses; red, yellow and blue; length 1,5 m with 1/4" SAE fitting, optional ball valves and 1 yellow charging line, length 1 m with 3/8" fitting. For R410A High Resistance hoses with Teflon gaskets. Red and blue hoses are fitted with a 5/16" nut at the curved side.

Manifold		Gauges Type	Reference			Scales		Refrigerants	
Valves	Other specs		Manifold	Dial	Option	bar	psi		
Central valve	Complete case	Dry	FR1108						
		Oil filled	FR1308						
		Pulse-free	FR1204						
		Without charging hoses	Dry	FR0208					
			Oil filled	FR0408					
			Pulse-free	FR0304					
				E01	x	x			R12+R22+R502
				E02	x	x			R134a+R404A
				E03	x				R22+R134a+R404A
				E04	x				R134a+R404A+R507+R407C
				E05	x	x			R290+R600
				E06	x				R22+R134a+R404A+R507
				E07	x				R134a+R407Cvap/liq
				E08	x				R22+R134a+R404A+R407Cvap/liq
			E09	x				R134a+R22+R409Avap/liq	
			E10	x				R22+R417Avap/liq	
			E11	x				R134a+R404A+R407Cvap/liq	
			E12	x				R134a+R22+R407Cvap/liq	
			E13	x				R507+R407Cvap/liq	
			E15	x				R410A	
			E16	x				R1270	
			E17	x				R410A+R22+R134a+R407Cvap/liq	
			E18	x				R744 (-1+20 Bar, -1+45 Bar)	
			E19	x				R744 (-1+30 Bar, -1+45 Bar)	
			E20	x				R744 (-1+30 Bar, -1+50 Bar)	
			E21	x				R410A+R22+R404A+R134a	
			E23	x				R23	
		E24	x				R407Cvap/liq+R410A+R22		
		E27	x				R410A+R407C+R404A+R134a		
				V	Option: Charging hoses length 1,5m with ball valve				
				VS	Option: Charging hoses length 1m with ball valve				

Bare body	Reference
Central valve	FR0104
4 valves	FR0104-4R

### How to read the tables?

The complete designation of a manifold comprises on one hand the references of the manifold and gauge and on the other hand the reference of the refrigerants.

Ex: 4 lane & central valve aluminium manifold, 80mm gauges, oil filled, charging hoses length 1m with ball valve, Refrigerants: R407C Vap.Liq.+R410A+R22: Manifold: FR1308; Refrigerants: E24; Reference: FR1308-E24-VS