



Blondelle vacuum gauge, Ø 80, composite case

High-end vacuum gauge



- High accuracy vacuum gauge
- Vacuum gauge: -760 mmHg to 0 or -1000 mbar to 0
- Pseudo-absolute: 0 +1000 mbar or 0 +1000 mbar/inHg
- Class 1, 'A Lame Acier'

- Ø 80, dry, oil filled or pulse-free
- Outlet: vertical or rear
- Fitting: 1/4" SAE or 1/8" NPT
- Options: safety valve, indicator hand, 1/4" SAE female fitting

Version	Outlet	Fitting	Reference			Scales	
			Case	Dial	Option	Vacuum gauge	Pseudo-absolute
Dry	Vertical	1/4" SAE	MA0603V14S			-760 mmHg tot 0 -1000 mbar tot 0	0+1000 mbar
		1/8" NPT	MA0603V18B				
	Rear	1/4" SAE	MA0603A14S				
		1/8" NPT	MA0603A18B				
Oil filled	Vertical	1/4" SAE	MA1003V14S				
		1/8" NPT	MA1003V18B				
	Rear	1/4" SAE	MA1003A14S				
		1/8" NPT	MA1003A18B				
Pulse-free	Vertical	1/4" SAE	MA0901V14S				
		1/8" NPT	MA0901V18B				
	Rear	1/4" SAE	MA0901A14S				
		1/8" NPT	MA0901A18B				
				6100			
				6104			
				6090			
						Description of the options	
						28	Safety valve
						01	Needle indicator
						45	1/4" SAE female fitting

How to read the tables?
 The complete designation of a vacuum gauge comprises the reference of the casing, followed by the reference of the dial.
 Ex: Vacuum gauge D80mm composite, dry, rear outlet, 1/4"SAE, 0+1000mbar, needle indicator, safety valve:
 Case: MA0603A14S; Dial: 6090; Option: 2801; Reference: MA0603A14S-6090-2801