

# VORTEX AC

All positive features in one recovery machine



- Compressor with ceramic bearings
- Single valve, liquid-tolerant, oil-less compressor
- 3 year warranty for the whole machine – the compressor, valve, fan and all other components.
- A unique brazed aluminium condensor provides better heat transfer
- Suitable for CFCs, HCFCs and HFCs, such as R410A
- Purging without changing hoses, thanks to its three-valve design
- Light, compact and well-balanced
- Individual valve assembly with dual-sealed valve stems eliminates leaks
- User-friendly
- 2 gauges: Blondelle Classe 1, 'A Lame Acier'

## SPECIFICATIONS

Refrigerants	CFC's, HCFC's en HFC's, incl. blends such as R410A
Weight	12,2kg
Dimensions	45,7cm * 24,1cm * 36,8cm
High-pressure shut-off	38 bar
Gauges	Class1 'A Lame Acier', Blondelle Low: -1 +20 bar High: -1 +45 bar
Compressor	0.25 kW, oil-less, single valve, AC-motor drive, ceramic bearings
Power	230V, 50/60 Hz
Certifications	CE, ARI 740-1998 Underwriters Laboratories Inc.
Warranty	3 years

## ACCESSORIES

714-202-G1	Base unit 230V, incl. sholderstrap, 1,8m power cord and user manual
------------	---

## PERFORMANCES ARI

Representative refrigerant	Category	Push-Pull kg/min (kg/h)	Liquid rate kg/min (kg/h)	Vapor rate kg/min (kg/h)
R134a	III	3,43 (205,8)	1,13 (67,8)	0,10 (6,0)
R22	IV	5,36 (321,6)	1,35 (81,0)	0,13 (7,8)
R410a	V	5,14 (308,4)	1,56 (93,6)	0,13 (7,8)

- Delivered with shoulder strap, 1,8m power cord and operating manual.